

# **PIPE FOR WATER PIPE AND THE LIKE**

## **FIELD OF THE INVENTION**

This invention relates to a pipe such as a water pipe and a supply-pipe that can  
5 improve water quality.

## **BACKGROUND OF THE INVENTION**

In the conventional pipe such as water pipe and supply pipe, the normal water  
pipe usually is used, and there is no improvement for water quality. Moreover, the  
10 quantity of chlorine is increased for water pollution and it is carried out the  
countermeasure with emphasis on disinfection and sterilization, they have developed  
into the social problem which is generated trihalomethane as carcinogenic substance  
including the problem of remains chlorine.

Moreover, as post-installation processing, the users attach the water cleaner and  
15 water-cleaner equipment, and they buy safe water in the supermarket etc.

Therefore, since there is no improvement for water quality in the conventional pipe  
such as water pipe and supply pipe, it costs greatly, and it is hard to attach the water  
cleaner and water-cleaner equipment.

Moreover, in order to attach the water cleaner and water-cleaner equipment in  
20 various types of the pipe body, pressure loss of the water pipe line is caused and it is  
difficult to get sufficient water flow speed.

## **SUMMARY OF THE INVENTION**

Accordingly, it is an object of the present invention to provide a pipe for water pipe  
25 and the like which can improve water quality efficiently and prevent degradation of a  
pipe. It is another object of the present invention to provide a pipe for water pipe and the

like which can be used in the large flow velocity region without pressure loss of the water pipe line.

Novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages thereof, are described below with reference to the accompanying drawings in which  
5 preferred embodiments of the invention are illustrated as an example.

It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only, and are not intended as a definition of the limits of the invention.

10

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a front view showing a first embodiment of the present invention;

Fig. 2 is a cross sectional view taken along the line 2-2 of Fig. 1;

Fig. 3 is a cross sectional view taken along the line 3-3 of Fig. 1;

15 Fig. 4 is a front view showing a second embodiment of the present invention;

Fig. 5 is a cross sectional view taken along the line 5-5 of Fig. 4;

Fig. 6 is a front view showing a third embodiment of the present invention;

Fig. 7 is a cross sectional view taken along the line 7-7 of Fig. 6;

Fig. 8 is a front view showing a fourth embodiment of the present invention;

20 Fig. 9 is a cross sectional view taken along the line 9-9 of Fig. 8;

Fig. 10 is a front view showing a fifth embodiment of the present invention; and

Fig. 11 is a cross sectional view taken along the line 11-11 of Fig. 10.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

25 Preferred embodiments of the present invention will be described in more detail below with reference to the accompanying drawings.

An understanding of the present invention may be best gained by reference to Figs. 1 - 3. Figs. 1 - 3 illustrate a pipe of the first embodiment of the present invention. The numeral 1 shows a pipe such as a water pipe and a supply-pipe and comprised of a pipe body 2 which is formed of steel material, metal material and the like used for water pipe, supply-pipe, drainage pipe and so on; and a mixed layer 6, including a mortar layer 4 and a resin layer 5, providing at an inner surface of the pipe body 2. The mortar layer 4 and resin layer 5 are mixed a mixture 3 including powder of tourmaline ore, granite and the like and charcoal grain powder with effects for far-infrared ray and anion.

When the tourmaline ore in the mixture 3 contacts water, weakly-alkalized (about pH 8) of water is carried out by causing electrolysis. Moreover, the hydroxide ion generated during electrolysis combines with a surrounding water molecule and turns into an anion (surface-active substance). Moreover, the molecule of water is subdivided by discharge of radiation (far-infrared ray) with 4-14-micrometer.

In the pipe 1 such as the water pipe, it is installed as usual. When water flows in the pipe 1, the pipe 1 is rubbed physically by water and produces an electrification action. The electrified electric charge discharges by touching water and electrolyzes water. Moreover, pressure change arises to the pipe 1 by change of water stream. This pressure change makes the mixed layer 6 to cause the piezo-effect and is electrified. The electrified electric charge discharges similarly and electrolyzes water.

The molecule ( $H_2O$ ) of water separates into a hydrogen ion ( $H^+$ ) and hydroxide ion ( $OH^-$ ) and is alkalized when the hydroxide ion ( $OH^-$ ) in water increases. However, since it is feeble current, the moisture approaches pH8 of weakly-alkali.

Moreover, the hydroxide ion ( $OH^-$ ) combines with the molecule of water and serves as a surface-active substance called hydroxyl ion ( $H_3O_2$ ). The hydroxyl ion makes a single molecule film and produces the surface-active effect. When hydroxyl ion goes into human's body, it acts on the parts with low resistance, and humors are adjusted to

weakly-alkalinity, and it makes metabolism active. Moreover, since surface-active water improves permeability and washing power, it is the best for cooking or washing.

In addition, when the above-mentioned pipe 1 is used, the water service institution entrepreneur may work as usual.

5        Other embodiments of the present invention will now be described with reference to Figs. 4 - 11. In Figs. 4 - 11, the same components as in the first embodiment described above with reference to Figs. 4 - 11 are designated by the same reference numerals and therefore will not be further explained in great detail.

10        A second embodiment of the present invention is shown in Figs. 4 - 5. It is distinguished from the first embodiment in that the mixed layer 6 is replaced from another mixed layer 6A which includes the mortar layer 4 which is mixed the mixture 3 including powder of tourmaline ore, granite and the like and charcoal grain powder with effects for far-infrared ray and anion. Accordingly, a pipe 1A according to the second embodiment will provide similar advantages to that according to the first  
15        embodiment.

      A third embodiment of the present invention is shown in Figs. 6 - 7. It is distinguished from the first embodiment in that the mixed layer 6 is replaced from another mixed layer 6B which includes the resin layer 5 which is mixed the mixture 3 including powder of tourmaline ore, granite and the like and charcoal grain powder  
20        with effects for far-infrared ray and anion. Accordingly, a pipe 1B according to the third embodiment will provide similar advantages to that according to the first embodiment.

      A fourth embodiment of the present invention is shown in Figs. 8 - 9. It is distinguished from the first, second and third embodiments in that the pipe body 2 is replaced from another pipe body 2A that is made of a synthetic resin such as polyvinyl  
25        chloride resin, including the mixture 3. Accordingly, a pipe 1C according to the fourth embodiment will provide similar advantages to that according to the first, second and

third embodiments.

A fifth embodiment of the present invention is shown in Figs. 10 - 11. It is distinguished from the fourth embodiment in that the mixed layer 6, 6A and 6B is not used. Accordingly, a pipe 1D according to the fifth embodiment will provide similar  
5 advantages to that according to the fourth embodiment.

Furthermore, although each embodiment differs mainly explained based on the first embodiment, when the composition used for each embodiment uses the present invention is combined, the same effect is achieved.

As set forth above, the advantages of the invention are as follows:

10 (1) The pipe for water pipe and the like includes a pipe body which is used for water pipe, supply-pipe, drainage pipe and the like; and a mixed layer, providing at an inner surface of the pipe body, mixing a mixture including powder of tourmaline ore, granite and the like and charcoal grain powder with effects for far-infrared ray and anion. Therefore, the water which flows the inside of a pipe can be energized efficiently.

15 Therefore, safe water can be always supplied anywhere even if it twists any faucet.

(2) As discussed above, since the mixed layer is formed in the inner wall of the pipe body, it can be prevented to generate rust easily.

(3) As discussed above, it can manufacture cheaply and easily.

(4) As discussed above, since it can be installed as usual, it can be used in the large  
20 flow velocity region without pressure loss of the water pipe line.

(5) Also claims 2, 3, 4 and 5 have the same effect as the above (1) to (4).